

ATON™ | SURGICAL

FIBER OPTIC HEADLIGHT POWERED BY HATTERAS



SEE BETTER
SEE FARTHER
SEE WHY



1971
2021

CELEBRATING
FIFTY YEARS OF
ILLUMINATION

SINCE 1971
ENHANCING
YOUR VISION

Powered by
Long Island
Technology
Group

AtoN™ SURGICAL

HIGH-INTENSITY SURGICAL FIBER OPTIC HEADLIGHT WITH ADJUSTABLE SPOT, POWERED BY HATTERAS LED LIGHT SOURCE

- Illumination Range with Hatteras: ~160,000 LUX at 16" (40 cm) to ~547,000 LUX at 10" (25 cm)
- Adjustable Iris Spot Diameter: .5"-4" (1.27 - 10.16 cm) at a working distance of 16" (40 cm)
- Color Rendering Index with Hatteras: 70 CRI
- Color Temperature with Hatteras: 5,400 K
- Standard Accompaniment: 10' Cobra Cable
- Hygienic Optic: Easy to Clean Twist-Off Feature
- Compatibility: ACMI Port
- Optic Weight: 1.5 oz (43.4g)



HATTERAS/AtoN SYSTEM

- Hatteras LED High-Intensity Surgical Light Source
- AtoN High-Intensity Headlight
- Choice of: Fiji or Key West Headband
- 10' Cobra Coil Cable
- Mobile Stand

AtoN HEADLIGHT SYSTEM PRODUCT CODES:

- BFW 1200 AtoN Headlight with Fiji Headband and 10' Cobra Coil Fiber Optic Cable
- BFW 1252 AtoN Headlight with Key West Headband and 10' Cobra Coil Fiber Optic Cable
- BFW 1255 AtoN Headlight with Fiji Headband and 10' Standard Fiber Optic Cable
- BFW 1257 AtoN Headlight with Key West Headband and 10' Standard Fiber Optic Cable
- BFW 1260 AtoN Headlight with Fiji Headband and 7' Standard Fiber Optic Cable
- BFW 1262 AtoN Headlight with Key West Headband and 7' Standard Fiber Optic Cable
- BFW 9860 7' AtoN Standard Fiber Optic Cable
- BFW 9865 10' AtoN Standard Fiber Optic Cable
- BFW 9866 10' AtoN Cobra Coil Fiber Optic Cable

EXCELLENT FOR USE IN THE FOLLOWING DEPARTMENTS

HOSPITAL

- CARDIOSURGERY
- NEUROSURGERY
- ORTHOPEDIC SURGERY
- PEDIATRIC SURGERY
- SPINE SURGERY
- THORACIC SURGERY
- TRANSPLANT SURGERY
- VASCULAR SURGERY

SURGERY CENTER

- ORTHOPEDIC SURGERY



ENGINEERED AND ASSEMBLED IN THE U.S.A.

HATTERAS TESTED AND CERTIFIED TO: IEC 60601-1-2 Edition 4, IEC 60601-2-18 Edition 3, ANSI/AAMI ES60601-1 (2005 + C1:09 + A2:10), CAN/CSA-C22.2 NO 60601-1- (2008), CE

ALL TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

© 2020 BFW, Inc.



BFWinc.com

800-717-4673 | +1-502-899-1808

445 BAXTER AVENUE | SUITE 175

LOUISVILLE, KY 40204 USA