

ATON™ | SURGICAL

FIBER OPTIC HEADLIGHT POWERED BY HATTERAS



SEE BETTER
SEE FARTHER
SEE WHY



SINCE
1971

CELEBRATING
FIVE DECADES
OF ILLUMINATION

AtoN™ SURGICAL

HIGH-INTENSITY SURGICAL FIBER OPTIC HEADLIGHT WITH ADJUSTABLE SPOT, POWER WITH BFW HIGH BRIGHT HATTERAS, S-MODEL HATTERAS OR CHROMAPRO

- Illumination Ranges at 16" (40 cm):
 - > High Bright Hatteras ~220,000 LUX
 - > S-Model Hatteras ~185,000 LUX
 - > ChromaPRO ~70,000 LUX
- Adjustable Iris Spot Diameter: .5"-4" (1.27 - 10.16 cm) at a working distance of 16" (40 cm)
- Fiber Optic Cables available in 7' and 10' lengths
- Hygienic Optic: Easy to Clean Twist-Off Feature
- Compatibility: ACMI Port
- Optic Weight: 1.5 oz (43.4g)

HATTERAS/AtoN SYSTEM

- Hatteras LED High-Intensity Surgical Light Source
- AtoN High-Intensity Headlight
- Choice of: Fiji or Key West Headband
- 10' Cobra Coil Cable
- Mobile Stand

AtoN HEADLIGHT SYSTEM PRODUCT CODES:

BFW 1200	AtoN Headlight with Fiji Headband and 10' Cobra Coil Fiber Optic Cable
BFW 1252	AtoN Headlight with Key West Headband and 10' Cobra Coil Fiber Optic Cable
BFW 1255	AtoN Headlight with Fiji Headband and 10' Standard Fiber Optic Cable
BFW 1257	AtoN Headlight with Key West Headband and 10' Standard Fiber Optic Cable
BFW 1260	AtoN Headlight with Fiji Headband and 7' Standard Fiber Optic Cable
BFW 1262	AtoN Headlight with Key West Headband and 7' Standard Fiber Optic Cable
BFW 9860	7' AtoN Standard Fiber Optic Cable
BFW 9865	10' AtoN Standard Fiber Optic Cable
BFW 9866	10' AtoN Cobra Coil Fiber Optic Cable

EXCELLENT FOR USE IN THE FOLLOWING DEPARTMENTS

HOSPITAL

CARDIOSURGERY
NEUROSURGERY
ORTHOPEDIC SURGERY
PEDIATRIC SURGERY
SPINE SURGERY
THORACIC SURGERY
TRANSPLANT SURGERY
VASCULAR SURGERY

SURGERY CENTER

ORTHOPEDIC SURGERY



BFWinc.com

800-717-4673 | +1-502-899-1808

445 BAXTER AVENUE | SUITE 175

LOUISVILLE, KY 40204 USA

Powered by
Long Island
Technology
Group



ENGINEERED AND ASSEMBLED IN THE U.S.A. © 2022 BFW, Inc.

ALL TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ATON TESTED AND CERTIFIED TO: ANSI/AAMI ES60601-1 (2005 + C1:09 + A2:10), CAN/CSA C22.2 NO 60601-1 Edition 2 (2008), CE

